



| | |
|-----------------|---|
| English | Dimensions according to DIN 43703 standard Electrical performance on CEI 13-6, IEC51, EN0051 Accuracy class: 0,25, 0.5, 1 and 2 (calibrated at 20 °C) Operating temperature: from -20 to 60 °C |
| Italiano | Dimensioni in accordo allo standard DIN 43703 Performance elettriche secondo CEI 13-6, IEC51, EN0051 Classi: 0.25, 0.5, 1 e 2 (taratura a 20 °C) Temperatura di operazione: -20 a 60 °C |
| Español | Dimensiones según estándar DIN 43703 Performance de acuerdo a CEI 13-6, IEC51, EN0051 Clase de precisión: 0.25, 0.5, 1, 2 (20 °C) Temperatura de operación: desde -20 a 60 °C |

Voltalge drop / Caduta di tensione/ Caída de tensión:

60 mV

| Model | Current [A] | Dimensions [mm] | | | | | | | | | Num. of terminals | Bolt |
|-------|-----------------|-----------------|----|----|---|---|----|----|-----|----|-------------------|--------|
| | | A | B | C | D | E | F | G | H | I | | |
| | 250 - 300 | 145 | 55 | 30 | - | - | 10 | 10 | 105 | 30 | 2 | M12x40 |
| | 400 - 500 - 600 | 145 | 55 | 40 | - | - | 10 | 10 | 105 | 30 | 2 | M16x45 |
| | 800 - 1000 | 165 | 65 | 60 | - | - | 10 | 10 | 115 | 30 | 2 | M20x50 |

100mV

| | | | | | | | | | | | | |
|--|-----------------|-----|----|----|---|---|----|----|-----|----|---|--------|
| | 250 - 300 | 168 | 55 | 30 | - | - | 10 | 10 | 128 | 30 | 2 | M12x40 |
| | 400 - 500 - 600 | 168 | 55 | 40 | - | - | 10 | 10 | 128 | 30 | 2 | M16x45 |
| | 800 - 1000 | 188 | 65 | 60 | - | - | 10 | 10 | 138 | 30 | 2 | M20x50 |

150mV

| | | | | | | | | | | | | |
|--|-----------------|-----|----|----|---|---|----|----|-----|----|---|--------|
| | 250 - 300 | 270 | 55 | 30 | - | - | 10 | 10 | 230 | 30 | 2 | M12x40 |
| | 400 - 500 - 600 | 270 | 55 | 40 | - | - | 10 | 10 | 230 | 30 | 2 | M16x45 |
| | 800 - 1000 | 290 | 65 | 60 | - | - | 10 | 10 | 240 | 30 | 2 | M20x50 |

BOSCO ELETTRONICA S.r.l

Sede Legale:

Via Giovanni Servais 176/2, 10146, Torino

Sede Operativa:

Via Alfiano 15/C, 10136, Torino

