



English	Dimensions according to DIN 43703 standard Electrical performance on CEI 13-6, IEC51, EN0051 Accuracy class: 0,25, 0.5, 1 and 2 (calibrated at 20 °C) Operating temperature: from -20 to 60 °C
Italiano	Dimensioni in accordo allo standard DIN 43703 Performance elettriche secondo CEI 13-6, IEC51, EN0051 Classi: 0.25, 0.5, 1 e 2 (taratura a 20 °C) Temperatura di operazione: -20 a 60 °C
Español	Dimensiones según estándar DIN 43703 Performance de acuerdo a CEI 13-6, IEC51, EN0051 Clase de precisión: 0.25, 0.5, 1, 2 (20 °C) Temperatura de operación: desde -20 a 60 °C

Voltalge drop / Caduta di tensione/ Caída de tensión:

**60 mV**

Model	Current [A]	Dimensions [mm]										Num. of terminals	Bolt
		A	B	C	D	E	F	G	H	I			
	1200 - 1500	165	65	90	21	48	10	10	115	30	4	M16x45	
	2000 - 2500	165	65	120	30	60	10	10	115	30			

100mV

	1200 - 1500	188	65	90	21	48	10	10	138	30	4	M16x45
	2000 - 2500	188	65	120	30	60	10	10	138	30		

150mV

	1200 - 1500	290	65	90	21	48	15	10	240	60	4	M16x45
	2000 - 2500	290	65	120	30	60	15	10	240	60		

**BOSCO ELETTRONICA S.r.l**

Sede Legale:

Via Giovanni Servais 176/2, 10146, Torino

Sede Operativa:

Via Alfiano 15/C, 10136, Torino

